

Amendments to the Claims

The claims are amended as follows:

1. (Currently Amended) A method, comprising:
 - parsing a data stream to find a predefined synchronization point within a packetized elementary stream (PES) packet in the data stream; and
 - placing non-compliant data in a stuffing bytes portion of the PES packet that is separate from the synchronization point and a payload in the PES packet;
 - wherein the data stream is decodable by a compliant decoder, after the non-compliant data is replaced with compliant data.
2. (Original) The method as recited in claim 1, further comprising:
 - encrypting a portion of the data stream; and
 - transmitting the portion of the data stream.
3. (Original) The method as recited in claim 2, further comprising:
 - decrypting the portion of the data stream.
4. (Original) The method as recited in claim 3, wherein the non-compliant data is key information that is used in encrypting and decrypting.
5. (Currently Amended) A method, comprising:
 - receiving a portion of a data stream;
 - parsing the portion of the data stream to find a synchronization point within a packetized elementary stream (PES) packet in the data stream;
 - retrieving non-compliant data in a stuffing bytes portion of the PES packet that is separate from the synchronization point and a payload in the PES packet;
 - replacing non-compliant data in the PES packet; and
 - decrypting the portion of the data stream.
6. (Original) The method as recited in claim 5, wherein the non-compliant data is key information that is used in decrypting.

7. (Previously Presented) The method as recited in claim 5, further comprising:
replacing the non-compliant data separate from the synchronization point with compliant data; and decoding the portion of the data stream.
8. (Currently Amended) A system, comprising:
an authoring device to use key information to encrypt a portion of a data stream, the key information being in a stuffing bytes portion of a packetized elementary stream (PES) packet that is separate from a synchronization point and a payload of ~~a packetized elementary stream (PES)~~ the PES packet in the data stream; and
a consumption device in communication with the authoring device, the consumption device to use the key information to decrypt the portion of the data stream and to replace key information with compliant data.
9. (Original) The system as recited in claim 8, further comprising:
a decoding device in communication with the consumption device to decode the portion of the data stream.
10. (Original) The system as recited in claim 8, wherein the consumption device is configured to retrieve the key information from the portion of the data stream.
11. (Currently Amended) A system, comprising:
an authoring device to create a data stream;
an encryption tool to embed key information in a stuffing bytes portion of a packetized elementary stream (PES) packet that is separate from each synchronization point and a payload ~~of a packetized elementary stream (PES)~~ the PES packet in the data stream and to encrypt a portion of the data stream associated with each synchronization point; and
a consumption device to retrieve key information separate from each synchronization point and the payload of the PES packet in the data stream and to replace the key information with compliant data and to use the key information to decrypt the data stream.
12. (Original) The system as recited in claim 11, further comprising:

a decoding device to decode the data stream.

13. (Original) The system as recited in claim 11, further comprising:
a decryption tool to use the key information to decrypt the portion.
14. (Currently Amended) A machine-accessible medium having associated content capable of directing the machine to perform a method, the method comprising:
parsing a first data stream to find a packetized elementary system (PES) header of a PES packet, the PES header associated with at least some payload data in the PES packet;
copying the first data stream to a second data stream; and
selectively inserting compliant data into in a stuffing bytes portion of the second data stream after the PES header and separate from the at least some payload data, to hold key information associated with the PES header.
15. (Previously Presented) The machine-accessible medium as recited in claim 14, wherein the method further comprises:
storing the first data stream; and
storing the second data stream.
16. (Original) The machine-accessible medium as recited in claim 14, wherein the method further comprises:
parsing the second data stream to find each PES header;
embedding key information into each portion of the second data stream after each PES header; and
encrypting each portion of the second data stream.
17. (Original) The machine-accessible medium as recited in claim 16, wherein the method further comprises:
transmitting each portion of the second data stream.

18. (Original) The machine-accessible medium as recited in claim 16, wherein the method further comprises:

- retrieving key information from a portion of the second data stream;
- decrypting the portion of the second data stream with the key information; and
- replacing the key information with compliant data in the portion of the second data stream.

19. (Original) The machine-accessible medium as recited in claim 18, wherein the method further comprises:

- decoding the portion.

20. (Currently Amended) A method, comprising:

- transmitting a packetized elementary stream (PES) packet to a consumption device, the PES packet including

- a header,

- key information in a stuffing bytes portion that is separate from and associated with the header for use in decryption, and

- a payload associated with the header and separate from the key information, the payload capable of being encrypted using the key information.

21. (Previously Presented) The method of claim 20, wherein compliant data replaces the key information associated with the header, before decryption.

22. (Previously Presented) The method of claim 21, wherein the header, compliant data, and decrypted payload are capable of being decoded by a compliant decoder.

23. (Previously Presented) The method of claim 20, wherein the key information in the header replaces compliant data, after encryption.

24. (Previously Presented) The method of claim 20, wherein the header is a packetized elementary stream (PES) header and the payload is a PES payload.

25. (Previously Presented) A machine-readable medium, having a set of instructions stored thereon, which when executed cause a machine to perform a set of operations comprising:
- transmitting a data structure to a consumption device, the data structure consisting of:
 - a header,
 - key information separate from and associated with the header for use in decryption, and
 - a payload associated with the header and separate from the key information, the payload capable of being encrypted the using key information.